


## OKTOPUS® GLASS-Jack GL-CC 1200 DES

Manipulator for handling large sized glass elements in combination with a mini crane or counterbalanced truck / variable reach forklift



### 2-circuit system

For construction site use according to DIN EN 13155

### Use

Handling flat glass panes on construction sites

### Hoist

Mini crane, counterbalanced truck, variable reach forklift

### Suspension

Exchangeable adapter for the connection with booms of different mini cranes and truck loading cranes, Forklift adapter with integrated powered side shift (+/- 100 mm) and powered telescopic boom (300 mm)

### Material to be handled

Flat glass, curved glass (concave or convex, bending radius  $\geq 2$  m) and window elements

### Description

The vacuum based load lifting attachment OKTOPUS® GLASS-Jack GL-CC 1200 DES is designed to handle glass panes and window elements at construction sites and with a maximum weight of 1200 kg.


It is equipped with a crane adapter to be mounted to a mini crane (provided by the customer). Alternatively the device can be attached to a counterbalanced truck / variable reach forklift by using the fork truck adapter. The suction frame can be tilted hydraulically by 120° and can be endlessly (360°) rotated motor driven as well as swiveled by  $\pm 40^\circ$ . All functions are operated with the help of a radio remote control. A 24 V DC operated vacuum pump generates the necessary negative pressure in the suction pads.

Deviations from the nominal condition are indicated by optical and acoustical warning equipment. Even in the case of complete failure of energy supply, vacuum remains for at least 5 minutes in each suction pad. In that way secure lowering of the load is ensured.



# OKTOPUS® GLASS-Jack GL-CC 1200 DES

Application data	
Working Load Limit:	Flat glasses: 800 kg (8 suction pads Ø 400 mm at the device) 1200 kg (12 suction pads Ø 400 mm at the device) Curved glasses: 1000 kg (20 suction pads Ø 280 mm at the device)
Own weight:	ca. 210 kg with suction frame for flat glass panes 8 pcs. suction pad Ø 400 mm ca. 240 kg with suction frame for flat glass panes 12 pcs. suction pad Ø 400 mm ca. 285 kg with suction frame for curved glass panes 20 pcs. suction pad Ø 280 mm
Lifting / Lowering:	by mini crane, counterbalanced truck or telescopic forklift
Movements suction frame:	
Rotate:	360°
Tilt:	0 - 120°
Swivel:	±40°
Suction pads:	8 resp. 12 pcs. Wirth Ø 400 mm / 20 pcs. Wirth Ø 280 mm, other pads on request
Vacuum generation:	Vacuum pump
Energy supply:	Quick exchange battery box, rechargeable battery, 24 V
Operation:	Radio remote control
Color:	RAL 2011 (deep orange), RAL 9006 (white aluminum)



Subject to change in the interest of technical progress.

DB119\_16 Ausg.: 03/18

## Headquarter

Wirth GmbH  
Brehnaer Straße 1  
D-06188 Landsberg  
Phone: +49 (0) 34 602 / 70 88 - 0  
Fax: +49 (0) 34 602 / 70 88 - 111

## Branch Office South

Wirth GmbH  
Nelkenstraße 11  
D-88074 Meckenbeuren  
Phone: +49 (0) 75 42 / 94 29 - 44  
Fax: +49 (0) 75 42 / 94 29 - 46

## E-Mail:

oktopus@wirth-gmbh.com  
info@wirth-gmbh.com

[www.wirth-gmbh.com](http://www.wirth-gmbh.com)

**WIRTH GMBH**  
EDGE PROFILES & VACUUM LIFTING TECHNOLOGY



MITGLIED IM  
**IFBS**